

Amendment to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

1. (currently amended) A display device comprising at least a first substrate, ~~forming part of~~ a display area, and at least one electrically controlled input device, characterized in that a first conductor pattern for driving said display area and a second conductor pattern for transmitting signals ~~from~~ from said electrically controlled input device are both arranged on said first substrate, wherein the device further comprises a second substrate, being positioned in parallel with and at a distance from said first substrate, at least one of said substrates being manufactured from a flexible material, wherein a layer of an electro-optically active material is arranged between said substrates in the display area, and wherein a plurality of conducting particles, having a diameter smaller than the distance between said substrates, are arranged between said substrates, in the area of said input device.

2.

2. (currently amended) A display device comprising at least a first substrate, a display area, and at least one electrically controlled input device, wherein a first conductor pattern for driving said display area and a second conductor pattern for transmitting signals from said electrically controlled input device are both arranged on said first substrate and ~~A display device as claimed in claim 1,~~ wherein said first conductor pattern and said second conductor pattern are arranged on a single side of said first substrate.

3. (canceled).

4. (canceled).

5. (currently amended) A display device as claimed in ~~claim 4~~, claim 1, wherein a conducting particle contacts the second conductor pattern on the substrate.

6. (previously amended) A display device as claimed in claim 1, wherein said first and second conductor patterns are manufactured from the same conductor material.

7. (currently amended) A display device as claimed in claim 1, wherein said first and second conductor patterns are manufactured from an essentially optically transparent conductor material.

8. (previously amended) A method for manufacturing a display device as claimed in claim 1, comprising the steps of:

- providing a first substrate;
- forming a layer of conductive material on an inner surface of said first substrate;
- patterning said layer of conductive material in order to generate a display area conductor pattern and an input device conductor pattern on said first substrate.

9. (currently amended) A method according to ~~claim 7~~, claim 8, wherein the step of patterning said layer of conductive material comprises the step of making said conductive patterns in a single processing step, ~~for example~~ by means of lithography.

10. (currently amended) A method according to ~~claim 8~~, claim 9 wherein the display device further comprises at least one external electrical connection, for accessing the display device from the outside, wherein the method further comprises simultaneously forming a conductive pattern for transmitting signals from said external electrical connection ~~is simultaneously formed~~ in the above-mentioned single processing step.